


URAIAN SINGKAT PEKERJAAN

Pengadaan ini merupakan Pengadaan CCTV Kampus Fakultas Kedokteran Universitas Andalas dengan nilai HPS Rp 164.328.840,-. Pengadaan CCTV Kampus Fakultas Kedokteran Universitas Andalas terdiri dari :

No	Item Name	Sepesifikasi Produk	Qty
1	Terpasang NVR 32 Channel Up 12 MP Hikvision 	Upto 32-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth Adopt Hikvision Acusense technology to minimize manual effort and security costs	1
2	Kamera indoor Colorvu Hikvision 2MP 	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m warm light, F1.0, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	37
3	Nvr 4 Chanel Hikvision 	256Mbps Bit Rate Input Max(up to 16-ch IP video),16x4MP decoding capability, 4 SATA Interfaces,2 HDMI ouputs(up to 8K),1 eSATA, alarm I/O: 16/9, 1.5U case,19"	1

4	Kamera Hikvision Outdoor 2 mP 	2 MP ColorVu MD 2.0 Fixed Bullet Network Camera High quality imaging with 2 MP resolution 24/7 colorful imaging Support Human and Vehicle Detection Water and dust resistant (IP67) Efficient H.265+ compression technology Support on-board storage up to 256GB	3
5	Hardisk CCTV 4TB dan 1 TB 	Form Factor: 3.5Inch Interface: SATA III 6Gb/s Kapasitas: 4 TB Rotation: 5400 RPM Cache: 256MB	2
6	Swich HUB POE SMART HIKVISION 8+2 	8 Port Fast Ethernet Unmanaged POE Switch 8 × 10/100Mbps PoE ports, and and 2 × Gigabit RJ45 port. IEEE 802.3at/af standard for PoE ports (Max. 60 W PoE output). IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell. Reliable fan-free design.	1

7	Switch HUB POE 16+2 	- Kategori: Power Over Ethernet Etalase: CCTV POE SWITCH HUB Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment	2
8	Swich HUB POE SMART HIKVISION 4+2 	4 Port Fast Ethernet Unmanaged POE Switch 4 x 10/100Mbps PoE ports, and and 2 x 10/100Mbps RJ45 ports. IEEE 802.3at/af standard for PoE ports (Max. 35 W PoE output). IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell. Reliable fan-free design.	1

9	Monitor Tv 43" 	monitor tv Full HD,HDMI 2, USB, Bezzel karaw	1
10	Kabel Lan 	Type : UTP 305 m cost-effective CAT6 CCA network cable Full diameter and full length Quality verified by Fluke test Guaranteed long PoE transmission distance UTP 4x2x23AWG/1 PVC, 305m CCA (Cooper content :27%)	8
11	Konektor RJ 45 	Conector Kabel RJ 45 untuk kabel lan	2

12	Rack Mount 9 U 	Panjang 530 mm Lebar 400 Mm Tinggi 450 mm pintu kaca	1
13	Monitor Tv 19 Inch 	"HD Resolution (1600 x 900) 100 Hz Refresh Rate V Shape Standing Bracket TN Panel HDMI & VGA Support Built-In Speaker 24/7 operation Physical button control mode High Contrast, Clear Details Low energy consumption, long service life Non-Bezelles Frame Vesa Mount	1
14	Duradus W Link 	Water Resistant Plastik 2 MM	40

15	Kabel Power 	-2,5 Rol Bahan Kawat13 x1	1
16	Fleksibel 	Pipa Fleksibel 4 Inch Warna putih	1
17	Steker dan Stop Kontak 	Plat Solid Palstic Gold	2

18	Duct Kabel 	Plastic 3Meter PVC	40
19	Klem Pipa dan Aksesoris Pendukung 	Plat Solid Plastic Gold	10